# Universal Grid RS-42X134-UG

1700 lb. WLL

OVERHEAD MEDIUM DUTY RIGGING FRAME

# RIGGING SYSTEM



**Universal Grid with Line Array** 

# RS-42X134-UG Medium Duty Universal Grid

Adaptive's Outdoor rated Universal Grid is a load-rated medium-duty frame designed to support overhead medium format loudspeakers, loudspeaker clusters and arrays.

Four upper hang points at each corner suspend up to the venue's superstructure and two side attach points provide for anti-sway cables. Lower suspension brackets, each with its own multiple hang point configurations allows for nearly any combination loudspeaker configurations.

This Universal Grid comes disassembled for ease of shipping and is constructed of structural tubular steel. It is then powder coated with a matte black finish.

Add the Universal Grid Extension RS-42X56-UG-EXT to rig full sub arrays behind the main array thus allowing the speaker cluster to increase it's down angle from the front.



#### **STANDARD FEATURES:**

- Permanently supports mid-size clusters and arrays
- Easy Installation goes together in minutes
- Rugged matte black powder coat finish
- Outdoor Rated

#### **OPTIONAL ACCESSORIES:**

- See overhead hardware data sheet
- See wire rope data sheet
- See safety cable data sheet
- RS-42X56-UG-EXT Frame Extension

# **SPECIFICATIONS:**

**Materials:** Structural steel **Finish:** Powder coat

Color: Black


**WLL:** 1400 lb / 636 kg using 4 rigging points **WLL:** 1700 lb / 773 kg using 6 rigging points


**Design Factor:** 5:1

Product Weight: 319 lb / 145 Kg

## **PACKAGE CONTENTS:**

1 pc. Universal Grid






# Adaptive Technologies Group

1635 E. Burnett Street | Signal Hill, CA 90755 USA Ph: 562.424.1100 | Fax: 562.424.3520 www.adaptivetechnologiesgroup.com



**Universal Grid** 



### ALWAYS INSTALL SAFETY CABLES

WARNING: Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.



