DUAL-AXLE PAN & TILT SPEAKER WALL MOUNT

MULTIMOUNT®



The MM-060-V2 Surround Wall Mount offers a smaller footprint compared with its predecessor, the MM-060 and keyhole slots in the wall mounting bracket allow for single-man installations.

Angle indicators show precisely where a speaker is aimed, saving the time needed to take acoustic measurements. Once the speaker is aimed in the desired direction, both pan and tilt angles lock down permanently.

These all-steel mounts are solidly constructed, install easily using hand tools and offer pan articulation up to 180 degrees and up to 45 degrees of down tilt adjustment.





STANDARD FEATURES:

- Infinite no-drift tilt adjustments.
- Single-Man installations
- Pan and tilt angles secured by clutch lock.
- Adapts to standard speaker hole patterns

OPTIONAL ACCESSORIES:

Safety Cable kits (See data sheets)

SPECIFICATIONS:

Material: Structural Steel Finish: Powder Coat

Color: Black

Tilt Adjustment: 45 degrees
Swivel Adjustment: 180 degrees

WLL: 60 lbs. (27.3 Kg) max. **Design Factor:** 5:1 ratio


Net Wgt: 6.1 lbs. (2.8 Kg.) each

Shipping Wgt: 8 lbs. (3.6 Kg.) each


Pack Count: 1 units/carton








7.29 90° MAX TILT ANGLE





Wall Mount Bracket

Speaker Mounting Bracket

Adaptive Technologies Group

1635 E. Burnett Street | Signal Hill, CA 90755 USA Ph: 562.424.1100 | Fax: 562.424.3520 www.adaptivetechnologiesgroup.com



ALWAYS INSTALL SAFETY CABLES

WARNING: Mounting and/or suspension of equipment requires experienced professionals. Improperly installed equipment can result in property damage, personal injury and/or liability to the installing contractor.