

BC-2824-12

(178.5 lb. WLL)

OFFSET BEAM CLAMP FOR 1/2-13 THREADED ROD

BEAM-WARE



BEAM CLAMP

Standard, pre-engineered channel style beam clamps anchor to a building's structure and offer a safe and predictable method of rigging grids and other objects from overhead. This hook style beam clamp is adjustable and mounts flush underneath the building's I-Beam's flange. Use the BC-2824-series hook style beam clamp to provide a load rated overhead rigging point from structural I-Beams with widths ranging between 2" and 6", 6" and 9" or 9" and 12".

This beam clamp model provides a fast, easy and safe way to rig direct loads, bridles and hitches from overhead and a hand wrench is all that is required to secure this clamp. The beam flanges must be parallel to the floor. The beam flanges must be parallel to the floor.



I-Beam with Clamp

KEY FEATURES:

- ▶ For beams with width between 9" and 12"
- ▶ Accommodates 1/2 - 13 threaded rod.
- ▶ For overhead vertical suspension applications.

OPTIONAL ACCESSORIES:

- ▶ See Threaded Rod Datasheet
- ▶ See Strut Accessories Datasheet
- ▶ See Sound Isolation Datasheet

SPECIFICATIONS:

Material: Structural Steel
Grade B7 Threaded Rod

Finish: Bright Zinc

Color: Silver

Design Factor: 7:1


WLL: 178.5 lbs / 81.1 Kg

Shipping Weight: 1.9 lbs / .78 Kg


PACKAGE CONTENTS:

- 1 pc** Beam Clamp
- 6 pcs** Hex Nut, 1/2-13
- 1 pc** 12" All Threaded Rod

Front View



Side View



Rated for indoor use.

ALWAYS INSTALL SAFETY CABLES

WARNING: Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.